

# MATERIAL SAFETY DATA SHEET

## Glue Machinery Corporation<sup>TM</sup>

4234 Boston Street, Baltimore, MD 21224

888-202-2468 · Fax: 410-761-5127 · E-mail: [info@gluemachinery.com](mailto:info@gluemachinery.com)

### CFA1012

#### SECTION 1 – GENERAL INFORMATION

**Product Name:** CFA1012 10oz – 24 pk  
**Product Use:** Reactive Hot Melt  
**CAS Number:** None  
**Date Issued:** 06/14/04  
**HMIS Hazard Rating:** Health: 2 Fire: 1 Reactivity: 1

#### SECTION 11 – COMPOSITION AND INFORMATION ON INGREDIENTS

<u>Hazardous Ingredients</u>	<u>CAS Number</u>	<u>Percent</u>
------------------------------	-------------------	----------------

**MATERIAL SAFETY DATA SHEET – CFA1012 (continued)**

**SECTION 111 – HAZARD IDENTIFICATION (continued)**

**INGESTION:**

No hazard is expected in normal industrial use. Do not eat, drink, or smoke around chemicals.

**MATERIAL SAFETY DATA SHEET – CFA1012 (continued)**

**SECTION V – FIRE FIGHTING MEASURES (continued)**

**EXTINGUISHING MEDIA:**

**MATERIAL SAFETY DATA SHEET – CFA1012 (continued)**

**SECTION V111 – EXPOSURE CONTROLS AND PERSONAL PROTECTION (continued)**

**ENGINEERING CONTROLS:**

Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

**RESPIRATORY PROTECTION:**

Atmospheric levels should be maintained below the exposure guidelines. For emergency and other conditions where an exposure guideline may be exceeded, use an approved positive-pressure self-contained breathing apparatus, or supplied air respirator with an auxiliary self-contained air supply.

**EYE PROTECTION:**

Use safety glasses.

**SKIN PROTECTION:**

Use impervious materials made of butyl or nitrile rubber where skin contact may occur.

**GENERAL:**

Safety shower and eye wash station.

**SECTION IX – PHYSICAL AND CHEMICAL PROPERTIES**

Form:	Solid
Appearance/Color:	White in solid state
Odor:	Mild
Solubility (in water):	N
pH value:	Not applicable
Boiling Range/Point:	Not applicable
Evaporation Rate:	
% Volatile:	0.0%
Specific Gravity:	1.16
VOC:	0 G/L

**SECTION X – STABILITY AND REACTIVITY**

Stability:	This product is stable
Hazardous Polymerization:	Hazardous polymerization will not occur

**CONDITIONS TO AVOID:**

Stable when stored under normal conditions. Decomposition begins at 350F (177C).

**INCOMPATIBILITY:**

Water, acids, bases, alcohols, metal compounds, and surface active materials. Avoid water as it reacts to generate heat, CO<sub>2</sub>, and insoluble urea. Some reactions may be vigorous.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Excessive heating can produce isocyanate vapor, mist and other hazardous organic compounds. Decomposition may occur with incompatible reactants, especially strong bases, water or temperatures over 320F (160C).

**MATERIAL SAFETY DATA SHEET – CFA1012 (continued)**

**SECTION XI – TOXICOLOGICAL INFORMATION**

This information has not been tested for toxicological effects.

**SECTION XII – ECOLOGICAL INFORMATION**

This information has not been tested for environmental effects.

**SECTION XIII – DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL:**

Disposal of this product must comply with all applicable federal, state and local regulations.